CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005 F.A.P. STP-3057(6)N



CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE (DESIGN-BUILD)



RESPONSIBILE CHARGE FOR THE DESIGN OF: ALL COMPONENTS OF THE PLANS PERTAINING TO LIGHTING, SIGNALS, SIGNAGE, AND PAVEMENT MARKINGS.

PROFESSIONAL CERTIFICATION

I CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO. EXPIRATION DATE:



801 South Caroline Street, Baltimore, Maryland 21231

RESPONSIBILE CHARGE FOR THE DESIGN OF: ALL COMPONENTS OF THE PLANS PERTAINING TO ROADWAY, STRUCTURES, DRAINAGE, EROSION & SEDIMENT CONTROL, AND MAINTENANCE OF TRAFFIC/DETOURS.

PROFESSIONAL CERTIFICATION

I CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND. LICENSE NO. EXPIRATION DATE:



RESPONSIBILE CHARGE FOR ALL COMPONENTS OF THE PLANS PERT

THE DESIGN OF: RTAINING TO LANDSCAPING.	1000	300	

TRADE CTR.

AQUARIUM

小部Inner Harbor

		LIMIT OF WORK	
 			
	LO	CATION MAP	
1000	0 500 1000		4000
		SCALE:	1"= 1000'

EASTERN AVENUE

%\Fells\\ Point

	INDEX OF SHEETS					
NO.	DGN.	DESCRIPTION				
1	TIO1	TITLE SHEET				
2	LG01	GENERAL NOTES, LEGEND AND ABBREVIATIONS				
3	GS01	GEOMETRIC LAYOUT				
4	TS01	TYPICAL SECTION AND DETAILS				
5	DE01	CONSTRUCTION DETAILS				
6 - 9	JN01, JD01-JD03	PAVEMENT JOINT NOTES AND DETAILS				
10-16	PS01-PS07	ROADWAY PLANS				
17-23	PR01-PR07	ROADWAY PROFILES				
24-43	SP01-SP20	STRUCTURAL PLANS				
44-49	E01-E06	CONDUIT PLANS				
50-55	W01-W06	WATER PLANS				
56-62	LD01-LD07	LANDSCAPE PLANS AND DETAILS				

TRAFFIC DATA	TRAFFIC DATA CENTR		
CONTROL / YEAR	2012	2032	
AVERAGE DAILY TRAFFIC (A.D.T.)	9.800	18,500	
DESIGN HOUR VOLUME (D.H.V.)	882	1.850	
% TRUCKS (A.D.T.)	2.5%	2%	
% TRUCKS (D.H.V.)	2.5%	2%	
DESIGN SPEED	35 MPH	35 MPH	

	FIELD BOOKS					
	NO.	DESCRIPTION				
	6931	TOPOGRAPHY				
	7972	TOPOGRAPHY				
	7799	TOPOGRAPHY				
Ì						

CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION

DRAFT SUBMITTAL

NOT FOR CONSTRUCTION

APPROVED

CONSTRUCTION DIVISION

APPROVAL RECOMMENDED

DIRECTOR, DEPARTMENT OF TRANSPORTATION

CHIEF, TRANSPORTATION ENGINEERING AND

DATE

DATE

BALTIMORE CITY REVIEW	R/W RELEASE	LIGHTING	TRAFFIC ENGINEERING	SIGNAL ENGINEERING	STRUCTURAL	CONDUIT	HIGHWAY ENGINEERING	DRAINAGE	EROSION AND SEDIMENT CONTROL	WASTE WATER ENGINEERING	WATER ENGINEERING	GRADE ESTABLISHED	TRANSPORTATION ENGINEERING
BY													
DATE													

GENERAL NOTES STANDARD SPECIFICATIONS: THE WORK UNDER THIS CONTRACT SHALL BE PERFORMED IN ACCORDANCE WITH ALL TERMS, CONDITIONS AND PROVISIONS OF THE STANDARD SPECIFICATION FOR CONSTRUCTION AND MATERIALS, MARYLAND DEPARTMENT OF TRANSPORTATION, STATE HIGHWAY ADMINISTRATION DATED JULY 2008. AS AMENDED, TOGETHER WITH ALL SPECIAL PROVISIONS INCLUDED IN THE PROPOSAL FORM. STANDARDS: THE WORK UNDER THIS CONTRACT SHALL BE PERFORMED IN ACCORDANCE WITH MARYLAND DEPARTMENT OF TRANSPORTATION, STATE HIGHWAY ADMINISTRATION BOOK OF STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES. 2. ALL BEARINGS AND COORDINATES ARE REFERRED TO THE TRUE MERIDIAN AND COORDINATE SYSTEM OF THE BALTIMORE CITY SURVEY CONTROL SYSTEM. ALL ELEVATIONS ARE REFERRED TO BALTIMORE CITY DATUM. 3. EXISTING UTILITIES: EXISTING UTILITY LOCATIONS SHOWN ON THE PLANS ARE APPROXIMATE. THE DESIGN-BUILDER SHALL CALL MISS UTILITY SEVENTY-TWO (72) HOURS BEFORE BEGINNING CONSTRUCTION. IT IS THE DESIGN-BUILDER'S RESPONSIBILITY TO VERIFY THE EXACT LOCATION OF UTILITIES BY TEST PITS PRIOR TO COMMENCING WORK. THE DESIGN-BUILDER SHALL VERIFY ALL DIMENSIONS SHOWN IN THE PLANS OF EXISTING FACILITIES PRIOR TO ORDERING ANY MATERIALS. ALL UTILITIES UNLESS OTHERWISE INDICATED, MUST BE KEPT ACCESSIBLE AND FULLY OPERABLE AT ALL TIMES. 4. THE DESIGN-BUILDER WILL BE REQUIRED TO COORDINATE WORK WITH ANY CONSTRUCTION BY UTILITY COMPANIES OR OTHER CONTRACTORS IN THE AREA.

5. SALVAGED MATERIALS: ALL SALVAGEABLE GRATES, FRAMES, AND COVERS FROM STORM WATER INLETS, MANHOLES, TREE PITS, ETC., WHICH WILL NOT BE RE-USED ON THE PROJECT SHALL BE SALVAGED AS BALTIMORE CITY PROPERTY. SIMILARLY, ALL TREE PLANTERS WHICH WILL NOT BE RE-USED ON THE

7. THE DESIGN-BUILDER SHALL MAINTAIN ACCESS TO ALL PROPERTIES WITHIN THE PROJECT LIMITS DURING

CONSTRUCTION. SPECIAL COORDINATION WITH THE PROPERTY OWNERS WILL BE INCIDENTAL TO THE COST OF THE PROJECT. ANY EXISTING CONDITIONS THAT HAVE TO BE ALTERED OR REMOVED FOR ACCESS SHALL

8. BACKFILL FOR UNSUITABLE MATERIAL SHALL BE VARIABLE DEPTH GRADED AGGREGATE BASE FOR BACKFILL.

THROUGHOUT ALL PHASES OF CONSTRUCTION. THE DESIGN-BUILDER SHALL BE REQUIRED TO PROVIDE

THE DESIGN-BUILDER IS REQUIRED TO NOTIFY STREET LIGHTING MAINTENANCE, MR. KENITH CHING AT

10. IF THE DESIGN-BUILDER UNCOVERS OR DAMAGES A STREET LIGHT CONDUIT OR CABLE DURING CONSTRUCTION,

410-396-1311 AND BGE IMMEDIATELY. STREET LIGHTING MAINTENANCE WOULD EFFECT REPAIRS OR DIRECT

BGE TO MAKE SAFE CONDITIONS AND/OR REPLACE CABLE PRIOR TO RESUMING CONSTRUCTION. ALL SUCH

11. DESIGN-BUILDER IS REQUIRED TO NOTIFY STREET LIGHTING MAINTENANCE, MR. KENITH CHING AT 410-396-1311,

TWO WEEKS PRIOR TO STARTING CONSTRUCTION. BGE MAY REQUIRE 30 DAYS NOTICE TO DE-ENERGIZE AND

RESPONSIBILITY OF THE DESIGN-BUILDER TO REMOVE AND DISPOSE OF EXISTING POSTS. THE DESIGN-BUILDER

12. THE DESIGN-BUILDER SHALL CONTACT THE PARKING AUTHORITY OF BALTIMORE CITY AT 443-573-2800 AND THE DEPARTMENT OF TRANSPORTATION METER SHOP AT 410-396-7576 TO VERIFY THE LOCATIONS OF EXISTING PARKING METERS OR E-Z PARK MACHINES. THE DESIGN-BUILDER MUST CONTACT THE PABC AND

THE METER SHOP 72 HOURS IN ADVANCE FOR THE REMOVAL OF PARKING METER HEADS. IT IS THE

MUST NOTIFY THE PABC 72 HOURS IN ADVANCE FOR THE REINSTALLATION OF PARKING METER POSTS

AND HEADS/E-Z PARK MACHINES. THE PABC WILL ARRANGE TO HAVE THE NEW POSTS AND E-Z PARK

13. THE DESIGN-BUILDER SHALL NOTIFY VEOLIA ENERGY AT 410-649-2464 IN ADVANCE OF ANY WORK THAT WILL

6. SHOP DRAWINGS: ALL SHOP DRAWINGS SHALL BE SEALED BY A MARYLAND LICENSED ENGINEER.

BE PUT BACK IN THEIR ORIGINAL CONDITION AND WILL BE INCIDENTAL TO CONSTRUCTION.

MAINTAINED DURING CONSTRUCTION.

REPAIRS SHALL BE MADE AT THE DESIGN-BUILDER'S EXPENSE.

MACHINE BÁSES TO BE DELIVERED TO THE DESIGN-BUILDER.

AFFECT VEOLIA STRUCTURES OR DISCHARGE PIPING.

RE-ENERGIZE LIGHTING SYSTEM PRIOR TO REMOVAL OF STREET LIGHT POLES.

9. ALL STREET LIGHTS, CABLES, CONDUITS, AND HAND BOXES MUST BE PROTECTED AND MAINTAINED

TEMPORARY LIGHTING AS PER BALTIMORE CITY STANDARDS IF THE EXISTING LIGHTING CANNOT BE

PROJECT SHALL BE SALVAGED AS BALTIMÓRE CITY PROPERTY. ALL SALVAGED ITEMS SHALL BE DELIVERED TO A CITY YARD AS DIRECTED BY THE ENGINEER. THE COST OF SALVAGING ITEMS WILL BE INCIDENTAL.

AI	BBREVIATIONS		
В	BENCH OF OUR		
BC BL	BOTTOM OF CURB BASELINE		BENCHMARK
BLDG	BUILDING		DENUMBARA
BW	BRICK WALK	V	
CAVITY	ABANDONED CELLAR ENTRANCE, COAL CHUTE, WINDOW WELL, ETC.	\triangle	CONTROL MONUMENT
СВ	CONCRETE BASE	WRA	
CC	CONCRETE CURB	+	FLY MONUMENT
CG	CONCRETE GUTTER	FĽY	
CL CL	CENTERLINE COMFORT LINK (UTILITY)	GPS	ODO MONUMENT
CMU	CONCRETE MASONRY UNIT	+	GPS MONUMENT
CP	CABLE POST	TRAV. NO.	TDAVEDOE MONUMENT
CO CONC	CLEAN OUT CONCRETE		TRAVERSE MONUMENT
CS	CONCRETE STEP		DOUBLE 14 IN ET
CW	CONCRETE WALK		DOUBLE K INLET
CV	CONCRETE VAULT		
DC DP	DEPRESSED CURB DOOR PROTECTOR		ROOF DRAIN
E	EXPANSION JOINT		
EB	ELECTRIC BOX	(D)	STORM DRAIN MANHOLE
EMH EX	ELECTRIC MANHOLE		
FB	EXISTING FLOWER BOX		SINGLE K INLET
FF	FINISHED FLOOR ELEVATION	∇	FIRE HYDRANT
FMH	FIRE MANHOLE		TINE TITONANT
G GC	GAS GRANITE CURB	(WM)	WATER METER
НВ	HANDBOX	WAT	
LP	LIGHT POLE	WAT	WATER MANHOLE
LT MAC	LEFT		WATER VALVE
MB	MACADAM MAIL BOX	GB	GAS BOX
MD	METAL DISK		
MH	MANHOLE	GAS PUMP	GAS PUMP
MP MR	METAL PLATE METAL RING	GM	GAS METER
MS	METAL SIGN	G	GAS MANHOLE
MTD	METAL TRAP DOOR		GAS VALVE
MV OC	METAL VENT ON CENTER	VENT	
ОН	OVERHEAD	G	GAS VENT
Ρ,	PIPE	CO	CANUTARY OF FAMOUR
P/C P.G.L.	POINT OF CROWN		SANITARY CLEANOUT
P.G.L. P/GE	PROFILE GRADE LINE PROFILE GRADE ELEVATION	(S)	SANITARY MANHOLE
P/GL	PROFILE GROUND LINE	VENT	
PM	PARKING METER		SANITARY AIR VENT
PP PR	PLASTIC PIPE PROPOSED	EJB	ELECTRICAL JUNCTION BOX
PVC	POLYVINYL CHLORIDE PIPE		
R	RAMP	(EM)	ELECTRIC METER
RS	RAIN SPOUT	E	ELECTRIC MANHOLE
RT SD	RIGHT STORM DRAIN		
SDMH	STORM DRAIN MANHOLE	\searrow	ELECTRIC POLE
SMH	SANITARY MANHOLE	EV	ELECTRIC VAULT
STMH STY	STEAM MANHOLE STORY	НВ	ELECTRIC HAND BOX
T	TELEPHONE		
TB	TELEPHONE BOOTH		ELECTRIC TRANSFORMER
TC TMH	TOP OF CURB TELEPHONE MANHOLE		GUY WIRE
TP	TRAFFIC POLE	\bigcirc	GUY POLE
TU	TELEPHONE UTILITY	\overline{T}	TELEPHONE MANHOLE
TYP	TYPICAL		
U UG	UNKNOWN UTILITY UNDERGROUND	\mathcal{O}	TELEPHONE POLE
V	VAULT	CTV	CABLE TV JUNCTION BOX
W	WATER		
WB WM	WOOD BENCH WATER METER	(STM)	STEAM MANHOLE
WMMH	WATER METER MANHOLE	(MH)	UNKNOWN MANHOLE
WVMH	WATER VALVE MANHOLE		
WVMV	WATER VALVE MAINVAULT		UNKNOWN UTILITY POLE
		\cap	

UNKNOWN VALVE

UTILITY MARKER

WARD-SECTION BLOCK

____XX.XX_____

BUILDING FACE

CONTOURS

UTIL

т т		NO.		REVISIONS DESCRIPTION	DATE
<u>L.f.</u>	EGEND				
<u>KISTING</u>				PROPOSED	
XX−XXX ∑	SOIL BORING LOCATION (CITY BALTIMORE CONTRACT TROOD	′ OF 17)——		COMBINATION CURB AND GUTTI (SEE PLANS FOR TYPE)	ER
PC-XXX	SOIL BORING LOCATION			CURB	
TH-XXX	TEST HOLE LOCATION (CITY BALTIMORE CONTRACT TROOO	OF 17)		FULL DEPTH PAVEMENT	
TH-XXX	TEST HOLE LOCATION				
	MONITOR WELL			MILL AND OVERLAY	
	LEFT TURN ARROW				
	LEFT-STRAIGHT ARROW			DRIVEWAY	
	RIGHT TURN ARROW			CONCRETE REMOVAL	
	RIGHT-STRAIGHT ARROW				
	STRAIGHT ARROW			SIDEWALK	
TP —	TRAFFIC SIGNAL POLE		32+00	CONSTRUCTION BASELINE	
	SIGN PEDESTRIAN SIGNAL		· •	PROPOSED TREE WELL	
	HANDICAP			THOI GOLD THEE WELL	
TRAF BOX	TRAFFIC CONTROL BOX BUSH		$\left(\begin{array}{c} + \end{array} \right)$	PROPOSED TREE	
Ews.	CONIFEROUS TREE			ELECTRICAL CONDUIT	
	DECIDUOUS TREE			ELECTRICAL MANHOLE	
	STUMP			FIRE HYDRANT	
	GROUND LIGHT		-Ω-	WATER VALVE	
	ROAD LIGHT POLE				
	YARD LIGHT				
	EXISTING ROADWAY LIGHTING				
FC	FILL CAP				
2	FLAG POLE				
	GATE, DOUBLE GATE, SINGLE				
MB	MAILBOX				
	BOLLARD				
PM O	PARKING METER				
	BRUSHLINE				
	HEDGEROW				
——————————————————————————————————————	FENCE OVERHEAD ELECTRIC				
<u>X"_RCP</u>	COMMUNICATIONS, CABLE		DRA	AFT SUBMITTAL	
X" SAN.	DRAIN PIPE UNDERGROUND ELECTRIC			OR CONSTRUCTION	
	SANITARY STEAM			CITY OF BALTIMORE	
X" GAS	GAS			DEPARTMENT OF TRANSPORTATIO CONTRACT NO. TR12317	N
X" W	WATER			SHA. NO. BC410005 F.A.P. STP-3057(6)N	-
T T	VERIZON RAIL ROAD				
	RAILROAD			TRAL AVENUE STREETSCAPE	

WR84

WHITMAN, REQUARDT & ASSOCIATES, LLP

EX

DRAWN BY: M.C.K. EXAMINED BY: N.Z.

SCALE: NOT TO SCALE DATE: MAY, 2013 TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION SHEET 2 OF 62

HARBOR POINT CONNECTOR BRIDGE

GENERAL NOTES, LEGEND

AND ABBREVIATIONS

LG01


DATE BY

	CONSTRUCT	ION CONTROL CO	ORDINATES	
CURVE	DESCRIPTION	NORTHING	EASTING	BEARING
	CONST	RUCTION CENTRAL AV	'ENUE	
	P.O.B. STA. 100+00.00	-5564.0155	4724.3207	N3° 16' 08.76"W
	P.C. STA. 102+82.83	-5281.6494	4708.1923	
CENTRAL-1	P.I. STA. 103+10.31	-5254.2090	4706.6250	
	P.T. STA. 103+37.80	-5226.7604	4705.2085	N2° 57' 14.91"W
	P.C. STA. 107+29.27	['] -4835.8063	4685.0332	
CENTRAL-2	P.I. STA. 107+50.79	-4814.3191	4683.9243	
	P.T. STA. 107+72.30	-4792.8368	4682.7230	N3° 12' 02.50"W
	P.C. STA. 116+71.09	-3895.4464	4632.5402	
CENTRAL-3	P.I. STA. 116+89.02	2 -3877.5522	4631.5395	
	P.T. STA. 117+06.94	-3859.6546	4630.6030	
	P.O.E. STA. 131+63.00	-2405.5829	4554.5173	N2° 59' 43.16"W

TRAVERSE POINTS							
POINT NO.	NORTHING	EASTING	STATION	OFFSET	ELEVATION		
114	-5533.6919	4415.0739	100+47.91	307.02 LT	10.31		
115	-5172.9942	4398.9752	104+07.28	303.06 LT	9.54		
116	-4804.0890	4369.6136	107+78.55	313.25 LT	8.00		
30242	-4474.9314	4620.4753	110+93.20	44.41 LT	7.67		
32557A	-4489.6210	4355.3640	110+93.26	309.93 LT	8.98		
100	-4096.9960	4593.2882	114+72.06	50.45 LT	9.07		
101	-3740.2589	4583.2964	118+28.65	41.01 LT	11.21		
102	-3519.3359	4564.4981	120+50.26	48.24 LT	12.06		
103	-3205.2484	4549.1353	123+64.72	47.17 LT	12.84		
104	-2895.7939	4535.8101	126+74.44	44.31 LT	16.33		
29955	-2635.5340	4521.9430	129+35.07	44.46 LT	18.47		

CURVE DATA								
CURVE	DELTA	Dc	R	L	Т	E		
CENTRAL-1	00° 18' 54" (RT)	00° 34' 23"	10,000.00'	54.97'	27.49	0.04		
CENTRAL-2	00° 14' 47" (LT)	00° 34' 23"	10,000.00'	43.03'	21.52	0.02		
CENTRAL-3	00° 12' 19" (RT)	00° 34' 23"	10,000.00'	35.84'	17.92	0.02'		





E 5100

REVISIONS

DATE BY

DESCRIPTION

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION
CONTRACT NO. TR12317
SHA. NO. BC410005
F.A.P. STP-3057(6)N

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE

GEOMETRIC LAYOUT

WHITMAN, REQUARDT
& ASSOCIATES, LLP
801 South Caroline Street, Baltimore, Maryland 21231

GLOWILTING LATOR

DRAWN BY: M.C.K.

EXAMINED BY: N.Z.


SCALE: AS SHOWN

DATE: MAY, 2013

TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET 3 OF 62

N:\31576-007\CADD\31576007H-GS01.dgn

GS01



LANDSCAPING

STA. 125+49 TO 127+52

P/GE, P/C SEE NOTE 1

EXISTING GRADE—

**MATCH GUTTER PAN SLOPE TO ROADWAY CROSS SLOPE REVISIONS

DESCRIPTION

DATE BY

LEGEND:

1 MODIFIED TYPE A COMBINATION CURB AND GUTTER (12" GUTTER PAN, 12" DEPTH, 6" CURB HEIGHT) – SEE DE01 FOR DETAIL AND PS01 THRU PS06 FOR LOCATIONS

NOTES:

- 1. SEE LANDSCAPE PLANS AND DETAILS ON SHEETS LS01 THROUGH LS07 FOR SIDEWALK AND MEDIAN TREATMENTS.
- WHERE SIDEWALK MEETS AN EXISTING BUILDING FACE OR WALL, A 1/2" EXPANSION JOINT MUST BE USED.

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

TS01

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION

CONTRACT NO. TR12317

SHA. NO. BC410005

F.A.P. STP-3057(6)N

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE

TYPICAL SECTION

TYPICAL SEC

SCALE: AS SHOWN DATE: MAY, 2013

RANSPORTATION ENGINEERING & CONSTRUCTION DIVISION SHEET 4 OF

DRAWN BY: M.C.K.


EXAMINED BY: N.Z.

O 2.5 5 10

WHITMAN, REQUARDT & ASSOCIATES, LLP 801 South Caroline Street, Baltimore, Maryland 21231

SCALE: AS SHOWN
TRANSPORTATION ENGINEERING & CONSTRU

TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET | 4 OF | 62 N:\31576-007\CADD\31576007H-TS01.dgn



N:\31576-007\CADD\31576007H-DE01.dgn

	REVISIONS		
Ю.	DESCRIPTION	DATE	BY

NOTES:

<u>GENERAL</u>

JOINTS SHALL BE CONSTRUCTED IN CONFORMANCE WITH THESE DETAILS, THE CONTRACT SPECIAL PROVISIONS, AND THE MDSHA STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIALS(JULY 2008). WHERE SPECIFIED, JOINTS SHALL BE CONSTRUCTED IN CONFORMANCE WITH THE MDSHA BOOK OF STANDARDS FOR HIGHWAY AND INCIDENTAL STRUCTURES.

THE CONTRACTOR SHALL SAWCUT CONTRACTION AND CONSTRUCTION JOINTS UNLESS SHOWN OTHERWISE. SAWING SHALL COMMENCE AS SOON AS CONCRETE HAS HARDENED SUFFICIENTLY TO PERMIT CUTTING THE CONCRETE WITHOUT CHIPPING. SPALLING, OR TEARING. TIMES MAY VARY DEPENDING ON WEATHER CONDITIONS AND/OR CURING TIME FOR THE MIX DESIGN.

SAWING INTO THE LOAD TRANSFER DEVICE OR WELDED WIRE REINFORCEMENT IS PROHIBITED.

CONSTRUCTION TRAFFIC SHALL NOT BE PERMITTED ON CONCRETE PANELS UNTIL JOINTS HAVE BEEN CONSTRUCTED AND THE CONCRETE HAS REACHED COMPRESSIVE STRENGTH OF 3000 PSI.

THE ASPHALT BASE AND ASPHALT SURFACE COURSES SHALL BE SAWCUT AT THE SAME LOCATIONS AS CONCRETE SAWCUTS. SEE JD03 FOR DETAILS, NOTES, TOLERANCES, ETC.

INSTALL ISOLATION JOINTS AROUND UTILITY MANHOLE COVERS, DRAINAGE INLETS, HANDBOXES, VALVES, METERS, ETC. THE PREFORMED ISOLATION JOINT FILLER MATERIAL SHALL BE CUT OFF AT THE TOP OF THE CONCRETE PAVEMENT, NO JOINT FILLER MATERIAL SHOULD EXTEND INTO THE ASPHALT PAVEMENT. ALL FIXTURES IN THE ROADWAY THAT ARE 12" IN DIAMETER OR SMALLER SHALL BE BOXED OUT AS SHOWN IN THE DETAILS. ALL FIXTURES GREATER THAN 12" IN DIAMETER SHALL NOT BE BOXED OUT. DUE TO THE UNCERTAINTY OF EXISTING FIXTURE LOCATIONS AND DIMENSIONS, THIS DESIGN ELEMENT IS NOT SHOWN IN THE JOINT LAYOUT PLAN. REFER TO THE DETAIL ON THIS SHEET, THE DETAILS ON JD02 AND JD03, AND MDSHA SPECIFICATIONS FOR MORE INFORMATION.

USE 10' MAX. AND 4' MIN. SPACING FOR CURB & GUTTER JOINTS. GENERALLY, BECAUSE SPACING FOR TRANSVERSE JOINTS IN ROADWAY IS 20', EVERY OTHER CURB & GUTTER JOINT SHOULD ALIGN WITH A TRANSVERSE JOINT. REFER TO THE DETAIL ON THIS SHEET AND MDSHA SPECIFICATIONS FOR MORE INFORMATION.

CURB & GUTTER SHALL BE TIED TO THE CONCRETE PANELS AS SHOWN ON DE01. EXPANSION MATERIAL SHALL BE PLACED BETWEEN BACK OF CURB AND SIDEWALK/BRICK PAVERS, BACK OF CURB AND DRIVEWAY, BACK OF CURB AND ANY OTHER STRUCTURE. REFER TO STD. NO. MD 655.01 FOR SIDEWALK DETAIL AND MDSHA SPECIFICATIONS FOR MORE INFORMATION.

JOINTS SHALL BE CONSTRUCTED VERTICALLY PERPENDICULAR TO THE FINISHED GRADE OF THE PAVEMENT.

JOINTS SHALL BE SEALED AS SHOWN ON JD03 AND AS SPECIFIED IN MDSHA SPECIFICATIONS.

TYPICAL JOINT SPACING

TYPICAL MAXIMUM SPACING BETWEEN JOINTS IS AS FOLLOWS:

TRANSVERSE JOINTS: 20'

LONGITUDINAL JOINTS: TRAVEL LANE - 10', MEDIAN LANE - 5'

JOINT TYPES

JOINT TYPES AND TERMINOLOGY ARE DEFINED IN THIS CONTRACT AS FOLLOWS:


<u>TYPE</u>	<u>NAME</u>	DETAILS	REMARK
TYPE A1 TYPE A2 TYPE B1 TYPE B2 TYPE C1 TYPE C2 TYPE D1 TYPE D2	TRANSVERSE CONTRACTION JOINT LONGITUDINAL CONTRACTION JOINT TRANSVERSE CONSTRUCTION JOINT LONGITUDINAL CONSTRUCTION JOINT THICKENED EDGE EXPANSION JOINT ISOLATION JOINT EX. PAVEMENT THICKENED EDGE JOINT NON—APPLICABLE	JN01, JD01, JD03 JN01, JD01, JD03 JN01, JD01, JD03 JN01, JD01, JD03 JN01, JD02, JD03 JD02, JD03	CONSTRUCT IN ACCORDANCE WITH 520.03.14(c)(1) OF MDSHA SPECIFICATIONS. CONSTRUCT IN ACCORDANCE WITH 520.03.14(c)(1) OF MDSHA SPECIFICATIONS. CONSTRUCT IN ACCORDANCE WITH 520.03.14(a) OF MDSHA SPECIFICATIONS. CONSTRUCT IN ACCORDANCE WITH 520.03.14(b) OF MDSHA SPECIFICATIONS
TYPE D3	UNPLANNED TRANSVERSE CONST. JOINT	JN01, JD02, JD03	TIED WITH DEFORMED STEEL TIE BAR. CONSTRUCT IN MIDDLE— THIRD OF SLAB AND IN ACCORDANCE WITH 520.03.14(a) OF MDSHA SPECIFICATIONS I.E. IN CASE OF EQUIPMENT BREAKDOWN.

REFER TO THIS SHEET AND JD01 THROUGH JD03 FOR MORE INFORMATION ON JOINT TYPES AND LOCATIONS.

THE USE OF TYPE B1 AND B2 JOINTS WILL DEPEND ON CONTRACTOR STAGING. TYPE B1 JOINTS MAY BE SUBSTITUTED FOR TYPE A1 JOINTS, AS NEEDED. LIKEWISE, TYPE B2 JOINTS MAY BE SUBSTITUTED FOR TYPE A2 JOINTS. TYPE A1 AND B1 JOINTS SHALL MATCH ADJACENT TRANSVERSE JOINTS. IF TYPE A1 OR B1 JOINTS CANNOT BE MATCHED TO ADJACENT TRANSVERSE JOINTS, REFER TO TYPE D3 DETAIL AND 520.03.14(a) OF MDSHA SPECIFICATIONS.

A TYPE C1 JOINT SHALL BE USED ALONG THE CENTRAL AVENUE BASELINE.

PROPOSED JOINTS SHALL ALIGN WITH ANY EXISTING JOINT SPACING REMAINING IN PLACE.



JOINT LAYOUT DETAIL SCALE: 1" = 5

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005

F.A.P. STP-3057(6)N


CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE


WR84 WHITMAN, REQUARDT & ASSOCIATES, LLP

JOINT NOTES & DETAILS


SCALE: AS SHOWN DATE: MAY, 2013 TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET 6 OF 62

JN01





PAVEMENT JOINT DETAIL NOT TO SCALE



TYPE A1 - TRANSVERSE CONTRACTION JOINT NOT TO SCALE


- REVISIONS DESCRIPTION DATE BY
- 2" HOT MIX ASPHALT SUPERPAVE 12.5 mm FOR SURFACE PG 76-22 LEVEL 2
- B 2" HOT MIX ASPHALT SUPERPAVE 19 mm FOR BASE PG 64-22 LEVEL 2
- 8" REINFORCED CEMENT CONCRETE PAVEMENT MIX NO. 7 SEE NOTE 8
- (D) 6" GRADED AGGREGATE BASE (GAB)
- E LONGITUDINAL JOINT AND DEFORMED STEEL TIE BAR -SEE DETAILS FOR TYPE A2 AND B2 JOINTS
- GEOTEXTILE_TYPE SE WOVEN (AASHTO M-288, CLASS 2)
- MODIFIED TYPE A COMBINATION CURB AND GUTTER, (G) 12" GUTTER PAN, 12" DEPTH, 6" RISE

- 1. A) REFER TO STD. NOS. MD-572.21 AND MD-572.23 FOR LÓAD TRANSFER DEVICE DETAILS AND NOTES. B) REFER TO SHEET JD03 FOR JOINT DETAILS AND NOTES. C) REFER TO STD. NO. MD-572.61 & MD-572.61-01 FOR TIÉ DEVICE DETAILS AND NOTES. D) WITHIN INTERSECTION BOX, USE #10 DEFORMED STEEL TIE BARS (GRADE 60), PLACE 12" C/C.
- 2. DOWEL BARS AND TIE-BARS SHALL BE EPOXY-COATED. SEE SECTION 908 OF THE MDSHA SPECIFICATIONS.
- 3. REFER TO SPECIAL PROVISIONS FOR DOWEL PLACEMENT TOLERANCES.
- 4. REFER TO MDSHA SPECIFICATIONS (SECTIONS 520, 523, 901, 908, 911, 915, 917, AND 921) AND THE SPECIAL PROVISIONS FOR MORÉ INFÓRMATION.
- 5. GEOTEXTILE SHALL BE PLACE WITH 2' OVERLAPS.
- 6. USE HIGH-EARLY STRENGTH CONCRETE MIX NO. 9 AS NEEDED TO MAINTAIN TRAFFIC AND DRIVEWAY ACCESS.

STEEL REINFORCEMENT OF CONCRETE PAVEMENT

SECTION B-B


NOT TO SCALE




NOT TO SCALE

- LOAD TRANSFER #10 SMOTH STEEL DOWEL BAR (GRADE 60) 10 BARS @ 12" SPACING C/C

SEE NOTES 1A, 2, & 3



TYPE B1 - TRANSVERSE CONSTRUCTION JOINT NOT TO SCALE



TYPE B2 - LONGITUDINAL CONSTRUCTION JOINT NOT TO SCALE

WR&A WHITMAN, REQUARDT & ASSOCIATES, LLP

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005 F.A.P. STP-3057(6)N

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE


JOINT NOTES AND DETAILS

SCALE: AS SHOWN DATE: MAY, 2013 TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET 7 OF 62

DRAWN BY: M.C.K. EXAMINED BY: N.Z.

N:\31576-007\CADD\31576007H-JD01.dgn


JD01



TYPE C1 - THICKENED EDGE EXPANSION JOINT

NOT TO SCALE

NOTES:
1. REFER TO JD02 FOR DETAILS AND NOTES.




<u>TYPE D3 - UNPLANNED TRANSVERSE CONSTRUCTION JOINT</u>

NOT TO SCALE


1. A) REFER TO STD. NO. MD-572.01 FOR TIE DEVICE DETAILS AND NOTES. B) REFER TO JD02 FOR DETAILS AND NOTES.


2. IF UNPLANNED TRANSVERSE JOINT OCCURS AT OR NEAR THE LOCATION OF A PLANNED TRANSVERSE JOINT, USE TYPE B1 JOINT. IF THE UNPLANNED TRANSVERSE JOINT OCCURS IN THE MIDDLE THIRD OF THE NORMAL JOINT INTERVAL, USE TYPE D4 JOINT.




TYPE D1 - FULL DEPTH PAVEMENT ADJACENT TO EXISTING PAVEMENT JOINT LONGITUDINAL SECTION


NOT TO SCALE





TYPE C2 - ISOLATION JOINT @ DRAINAGE STRUCTURE NOT TO SCALE





TYPE C2 - ISOLATION JOINT @ UTILITY COVER

1' DIA. OR LESS

NOT TO SCALE

2" HOT MIX ASPHALT SUPERPAVE 12.5 mm FOR SURFACE PG 76-22 LEVEL 2

- B 2" HOT MIX ASPHALT SUPERPAVE 19 mm FOR BASE PG 64-22 LEVEL 2 C 8" REINFORCED CEMENT CONCRETE PAVEMENT MIX NO. 7 SEE NOTE 8

REVISIONS

DESCRIPTION

DATE BY

- (D) 6" GRADED AGGREGATE BASE (GAB)
- E) GEOTEXTILE TYPE SE WOVEN (AASHTO M-288, CLASS 2)

- 1. A) REFER TO STD. NO. MD-572.21 FOR LOAD TRANSFER DÉVICE DETAILS AND NOTES. B) REFER TO SHEET JD03 FOR JOINT DETAILS AND NOTES. C) REFER TO STD. NO. MD-572.61 & MD-572.61-01 FOR TIE DEVICE DETAILS AND NOTES.
- 2. DOWEL BARS AND TIE-BARS SHALL BE EPOXY-COATED. SEE SECTION 908 OF THE MDSHA SPECIFICATIONS.
- 3. REFER TO SPECIAL PROVISIONS FOR DOWEL PLACEMENT TOLERANCES.
- 4. REFER TO MDSHA SPECIFICATIONS (SECTIONS 520, 523, 901, 908, 911, 915, 917, AND 921) AND THE SPECIAL PROVISIONS FOR MORE INFORMATION.
- 5. GEOTEXTILE SHALL BE PLACE WITH 2' OVERLAPS.
- 6. IF UNPLANNED TRANSVERSE JOINT OCCURS AT OR NEAR THE LOCATION OF A PLANNED TRANSVERSE JOINT, USE TYPE B1 JOINT. IF THE UNPLANNED TRANSVERSE JOINT OCCURS IN THE THIRD OF THE NORMAL JOINT INTERVAL, USE TYPE D3 JOINT.
- 7. USE HIGH-EARLY STRENGTH CONCRETE MIX NO. 9 AS NEEDED TO MAINTAIN TRAFFIC AND DRIVEWAY ACCESS.

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005

JD02

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE

UR&A

JOINT NOTES AND DETAILS

F.A.P. STP-3057(6)N

SCALE: AS SHOWN DATE: MAY, 2013 TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET 8 OF 62

DRAWN BY: M.C.K. EXAMINED BY: N.Z.

N:\31576-007\CADD\31576007H-JD02.dgn

REVISIONS DESCRIPTION DATE BY


- HOT-APPLIED


RUBBER ASPHALT JOINT SEALER


BOND BREAKER
TAPE

-SAWCUT AS NECESSARY

SEE NOTE 4







SEAL METHOD 1 TRANSVERSE/LONGITUDINAL JOINTS

DRAWN BY: M.C.K.

EXAMINED BY: N.Z.

SEAL METHOD 2 TOOLED CONSTRUCTION JOINT

SEAL METHOD 3 EXPANSION/ISOLATION JOINT

JOINT TYPE	SEAL METHOD	T CONC. SLAB THICKNESS	W RESEVOIR WIDTH	S SEAL THICKNESS	D1 INITIAL SAWCUT DEPTH	D2 RESEVOIR DEPTH
A1*	1			,	T/3	
A2	1	8" FOR	4 /4"	4 /4" 14151	SEE NOTE 2	1 1 / / "
B1*	1,2	ROADWAY	1/4"	1/4" MIN.		1-1/4"
B2	1,2	SLABS				
C1	3		3/4"	3/8" MIN.	INITIAL SAWCUT	2"
C2	3		1/2"		NOT	1-1/2"
D1	2			 1/4" MIN.	REQUIRED	
D2	2		1/4"	1/4 WIIN.		1-1/4"
D3	2					
*SEE	NOTE 5					

SAWCUTTING AND SEALING OF JOINTED REINFORCED CONCRETE PAVEMENT

- 1. INITIAL SAWCUTS SHALL COMMENCE AS SOON AS CONCRETE HAS HARDENED SUFFICIENTLY TO PERMIT CUTTING THE CONCRETE WITHOUT CHIPPING, SPALLING, OR TEARING. TIMES MAY VARY DEPENDING ON WEATHER CONDITIONS AND/OR CURING TIME FOR THE MIX DESIGN. HOWEVER, THE INITIAL SAW CUT SHALL BE COMPLETED WITHIN 24 HOURS AFTER PLACEMENT OF CONCRETE.
- 2. SAWING INTO DOWEL BARS, TIE BARS, OR WELDED WIRE REINFORCEMENT IS PROHIBITED.
- 3. JOINTS SHALL BE THOROUGHLY CLEANED AND DRYED AS PER SECTION 523.03.02 OF THE MDSHA SPECIFICATIONS BEFORE INSTALLATION OF THE SEAL.
- 4. SEAL METHODS 1 AND 2 SHALL USE SILICONE JOINT SEALER AS PER SECTION 911.01.01 OF THE MDSHA SPECIFICATIONS.
- SEAL METHOD 3 SHALL USE HOT-APPLIED RUBBER ASPHALT JOINT SEALER AS PER SECTION 911.01 AND PREFORMED JOINT FILLER AS PER SECTION 911.02.
- 5. FOR TYPE A1 AND B1 TRANSVERSE JOINTS, THE DESIGN—BUILDER MAY USE PREFORMED POLYCHOROPRENE ELASTOMERIC COMPRESSION JOINT SEALS AS PER SECTION 911.04 OF THE MDSHA SPECIFICATIONS. DESIGN—BUILDER SHALL SUBMIT INSTALLATION METHODS AND DETAILS TO BALTIMORE CITY FOR APPROVAL. DETAILS SHALL INCLUDE CROSS SECTIONAL DESIGN AND RESEVOIR DIMENSIONS.
- 6. REFER TO SECTION 523 OF THE MDSHA SPECIFICATIONS FOR MORE INFORMATION.

SAWCUTTING AND SEALING OF ASPHALT

DRAFT SUBMITTAL **NOT FOR CONSTRUCTION**

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005 F.A.P. STP-3057(6)N

CENTRAL AVENUE STREETSCAPE AND

JOINT NOTES AND DETAILS

WR&A WHITMAN, REQUARDT & ASSOCIATES, LLP

HARBOR POINT CONNECTOR BRIDGE

SCALE: AS SHOWN DATE: MAY, 2013 TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION SHEET 9 OF 62

N:\31576-007\CADD\31576007H-JD03.dgn

JD03

1. BEFORE INSTALLATION OF THE SEALER, SAWCUTS SHALL BE THOROUGHLY CLEANED AND DRYED.

2. JOINTS SHALL BE SEALED WITH HOT-APPLIED RUBBER ASPHALT JOINT SEALER AS PER 911.01 OF THE MDSHA SPECIFICATIONS AND THE SPECIAL PROVISION.

3. SAWCUTS IN THE ASPHALT BASE AND SURFACE COURSES SHALL ALIGN WITH THE CENTERLINE OF CONCRETE JOINT WITHIN 1".

4. IF THE HMA SURFACE COURSE IS TO BE PLACED THE FOLLOWING PAVING SEASON, SAWCUT THE HMA BASE COURSE TO PROVIDE A 1" DEEP BY 1/8" WIDE CHANNEL TO FACILITATE AND CONTROL REFLECTIVE CRACKING. DO NOT SEAL.


5. REFER TO THE SPECIAL PROVISION FOR MORE INFORMATION.


ASPHALT ROADWAY SURFACE -


ASPHALT BASE COURSE SURFACE -


CONCRETE PAVEMENT SURFACE --


~ 8" JOINTED REINFORCED
















REVISIONS DESCRIPTION DATE BY 1. CONSTRUCTION LIMITS ON CROSS STREETS SHOWN ON CROSS REFERENCES THIS PLAN ARE CONCEPTUAL AND SHALL BE CONSIDERED DWG. NO. ITEM AS THE MINIMUM REQUIRED. THE CONSTRUCTION LIMITS SHALL BE DETERMINED BASED ON THE REQUIRED HORIZONTAL TYPICAL SECTIONS TS01 AND VERTICAL CHANGES AS WELL AS FIELD CONDITIONS. GEOMETRIC LAYOUT GS01 ROADWAY PROFILES PR06 2. LINING OF EXISTING STORM DRAIN CULVERT FROM EASTERN AVE E06 CONDUIT PLANS TO MADISON STREET IS BEING PERFORMED UNDER BALTIMORE LS06 LANDSCAPE PLANS CITY CONTRACT TR 08310 3. SEE LANDSCAPING PLAN LD07 FOR LOCATION AND REQUIREMENTS OF BRICK PAVING. 4. COORDINATE WITH THE CONTRACTOR OF TR08310 FOR INSTALLATION OF NEW TREE PITS AND PLATING TREES. E 4400 WATSON 1339 4 N. CENTRAL AVE. 1362/ 3-3 1157 E. BALT. ST; (31) 4 S. CENTRAL AVE. SEE NOTE 1-1150 LOMBARD ST. JAMES M. GREEN 20 S. CENTRAL AVE. BALTIMORE RESCUE MISSION, INC. THE JEWISH MUSEUM OF MARYLAND INC 1159 E. BALT. SE (32) MEDD PROPERTIES II _ SEE NOTE 4 BEICK BAIL WOR SUITSING EXISTING ROW LINE EXISTING ROW LINE XISTING ROW LINE - SEE NOTE · - B CONSTRUCTION CENTRAL AVENUE - SEE NOTE 2 131+00 130+00 CENTRAL AVENUE - SEE NOTE 4 EXISTING ROW LINE+ EXISTING ROW LINE AISTING ROW LINE 7 SOUTH CENTRAL 1 1300 E. BALTIMORE STREET 3-2 DAY'S AUTO BODY 3-2 LIMIT OF WORK CENTRAL AVENUE STA. 131+63.00 1301 E. BALTIMORE STREET 39 S. CENTRAL AVE. 2 1302 E. BALTIMORE STREET 11 S. CENTRAL AVE. 3-2 MITEY LLC 18 DURON, INC. C/O SHERWIN - WILLIAMS CO. 3 1304 E. BALTIMORE STREET 4 1306 E. BALTIMORE STREET 67.77' R.O.W. E 4700 **DRAFT SUBMITTAL LEGEND** NOT FOR CONSTRUCTION PS07 CURB & GUTTER MILL & OVERLAY CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005 F.A.P. STP-3057(6)N FULL DEPTH SIDEWALK DRIVEWAY CENTRAL AVENUE STREETSCAPE AND CONCRETE/ASPHALT REMOVAL HARBOR POINT CONNECTOR BRIDGE ROADWAY PLAN TREE REMOVAL STA. 129+50 TO STA. 131+63 **UR**®A DRAWN BY: M.C.K. WHITMAN, REQUARDT & ASSOCIATES, LLP SCALE: 1"=20' DATE: MAY, 2013 SCALE: 1"= 20' EXAMINED BY: N.Z. TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET 16 OF 62 N:\31576-007\CADD\31576007H-PS07.dgn






HARBOR POINT CONNECTOR BRIDGE: CENTRAL AVENUE TO HARBOR POINT SCALE: HORIZ.: 1"=20' VERT.: 1"=4'

RETAINING WALL SECTIONS

SCALE: HORIZ.: 1''=5' VERT.: 1''=5'



10/15/2012 \\RKKM\v2009\2009\09164_HARBORPT\\Task03.07-CA Bridge Concept\CADD\DESIGN\PR01_Ce

Rummel, Klepper & Kahl,LLP 81 MOSHER STREET | BALTIMORE, MD 21217 PH: (410) 728-2900 FAX: (410) 728-3160

www.rkk.com

30% SUBMITTAL

NOT FOR CONSTRUCTION


CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE

ROADWAY PROFILE & RETAINING WALL SECTIONS STA. 101+84.24 TO STA. 97+30.00


Engineers | Construction Managers | Planners | Scientists | SCALE: AS NOTED

DATE: OCT. 15, 2012 SHEET 17 OF 62

PR-01




N:\31576-007\CADD\31576007H-PR02.dgn




REVISIONS DESCRIPTION DATE BY 28 26 © Bank Street EXISTING GROUND LINE — 117+00 DRAFT SUBMITTAL NOT FOR CONSTRUCTION PR04 CENTRAL AVENUE - LANCASTER STREET TO WATSON STREET CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005 F.A.P. STP-3057(6)N CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE SCALE: 1"= 2' ROADWAY PROFILE STA. 112+00 TO STA. 117+50 WR84 SCALE: 1"= 20' DRAWN BY: M.C.K. WHITMAN, REQUARDT & ASSOCIATES, LLP 801 South Caroline Street, Baltimore, Maryland 21231 SCALE: 1"=20' DATE: MAY, 2013 EXAMINED BY: N.Z. TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION SHEET 20 OF 62


N:\31576-007\CADD\31576007H-PR04.dgn




N:\31576-007\CADD\31576007H-PR05.dgn



REVISIONS DESCRIPTION DATE BY XX/XX XXX 1 DESCRIPTION 1 XX/XX XXX 2 DESCRIPTION 2





WR&A

W HIT MAN, REQUARDT & ASSOCIATES, LLP 801 South Caroline Street, Baltimore, Maryland 21231



PR07

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005 F.A.P. STP-3057(6)N

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE


ROADWAY PROFILE

STA. 129+50 TO STA. 131+63

SCALE: 1"=20'

DATE: MAY, 2013 TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION SHEET 23 OF 62

N:\\31576-007\CADD\\31576007H-PR07.dgn



REVISIONS

DESCRIPTION

DATE BY

LEGEND:



EXISTING STRUCTURE TO BE REPLACED

EXISTING STRUCTURE TO REMAIN

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

SP01

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION

CONTRACT NO. TR12317

SHA. NO. BC410005

F.A.P. STP-3057(6)N

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE


STRUCTURE LOCATION MAP



SCALE: AS SHOWN DATE: JANUARY, 2014

TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET 24 OF 62

N:\31576-007\CADD\Bridge\31576007GP05.dgn



REVISIONS DATE BY DESCRIPTION

GENERAL NOTES

SPECIFICATIONS:

STEEL:

ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH SHA SPECIFICATIONS DATED 2008, INCLUDING ALL REVISIONS THEREOF AND ADDITIONS THERETO AND

SPECIAL PROVISIONS FOR MATERIALS AND CONSTRUCTION.

CONCRETE DESIGN: LOAD AND RESISTANCE FACTOR (LRFD) DESIGN

AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS DATED 2012 (6th EDITION)

REINFORCING STEEL DESIGN: Fy = 60,000 PSI.

LOADING: HL-93 PLUS 2" FUTURE WEARING SURFACE.

ALL CONCRETE FOR TOP SLAB SHALL BE MIX NO. 6 (4,500 PSI). ALL OTHER **CONCRETE:**

CONCRETE SHALL BE MIX NO. 3 (3,500 PSI.)

REINFORCING STEEL SHALL CONFORM TO A 615, GRADE 60. ALL SPLICES, REINFORCING NOT SHOWN, SHALL BE LAPPED AS PER BAR LAP CHARTS. MINIMUM

COVER FOR ANY BAR SHALL BE 2" UNLESS OTHERWISE NOTED, WITH THE EXCEPTION OF BARS AT THE BOTTOM AND SIDES OF ALL FOOTINGS

WHICH SHALL HAVE 3" MINIMUM COVER.

FOR TIES AND STIRRUPS; STANDARD ACI BENDING TOLERANCES ARE MODIFIED TO PLUS (+) ZERO INCHES, MINUS (-) NORMAL ACI

BENDING TOLERANCE'S.

ONLY GRADE 60 CAN BE USED ON THIS PROJECT

ALL REINFORCING STEEL IN THE TOP MAT OF THE TOP SLAB INCLUDING TRUSS BARS SHALL BE EPOXY COATED.

ALL KEYS ARE NOMINAL SIZE. KEYS:

ALL DIMENSIONS AFFECTED BY THE GEOMETRICS, AND/OR EXISTING STRUCTURE EXISTING STRUCTURE:

SHALL BE CHECKED IN THE FIELD BY THE CONTRACTOR, BEFORE ANY CONSTRUCTION IS DONE, AND BEFORE ANY REINFORCING STEEL, ETC., IS ORDERED AND FABRICATED. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO SUPPLY THE ENGINEER WITH ALL FIELD DIMENSIONS REQUIRED TO CHECK DETAIL DRAWINGS. THE ± MARKS SHOWN WITH DIMENSIONS AND STATIONS DO NOT INDICATE ANY DEGREE OF PRECISION. THESE MARKS (±) INDICATE EXISTING DIMENSIONS AND STATIONS THAT MAY VARY AND DO REQUIRE FIELD VERIFICATION BY THE CONTRACTOR.

EXISTING STRUCTURE SHOWN IN LONG DASHED LINES.

PORTIONS OF EXISTING STRUCTURES SHOWN HATCHED, TO BE REMOVED.

FOR THE CONVENIENCE AND INFORMATION OF BIDDERS, PRINTS OF PLANS **EXISTING PLANS:**

OF THE EXISTING PERTINENT STRUCTURES ARE AVAILABLE AT THE CITY OF BALTIMORE, DEPARTMENT OF TRANSPORTATION, FOR THE CONTRACTOR'S REVIEW. NO RESPONSIBILITY FOR THEIR ACCURACY OR COMPLETENESS IS ASSUMED BY THE CITY OF BALTIMORE, DEPARTMENT OF TRANSPORTATION.

DIMENSIONS, DETAILS, ETC. AS SHOWN THEREON MAY NOT BE "AS BUILT"

UTILITIES: THE DESIGN-BUILDER IS RESPONSIBLE FOR IDENTIFYING, LOCATING, AND RELOCATING, AS NECESSARY, ALL EXISTING UTILITIES WITHIN THE PROJECT

AREA. THE UTILITIES SHOWN HEREON ARE FOR REFERENCE ONLY AND THE CITY OF BALTIMORE, DEPARTMENT OF TRANSPORTATION, TAKES NO RESPONSIBILITY FOR THE COMPLETENESS OR ACCURACY OF THE UTILITY INFORMATION SHOWN HEREON. UTILITIES SHOWN ARE BASED ON FIELD SURVEY INFORMATION. NO TEST-PITS

WERE PERFORMED TO DETERMINE VERTICAL LOCATION OF UTILITIES SHOWN.

1. THE STAGING LIMITS SHOWN ARE SUGGESTED AND THE DESIGN-BUILDER SHALL MAKE THEIR OWN DETERMINATION OF THE REQUIRED STAGING LIMITS. IT IS THE RESPONSIBILITY OF THE DESIGN-BUILDER TO CONFIRM THAT THEIR PROPOSED LIMITS OF STAGING MEET ALL OF THE REQUIRED STRUCTURAL AND MAINTENANCE OF TRAFFIC PROVISIONS STIPULATED IN THE SPECIAL PROVISIONS.

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

SP02

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005 F.A.P. STP-3057(6)N

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE

GENERAL PLAN AND ELEVATION ALICEANNA STREET OVER HARFORD RUN


UR®A


WHITMAN, REQUARDT & ASSOCIATES, LLP

SCALE: AS SHOWN DATE: JANUARY, 2014

TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION SHEET 25 OF 62 N:\31576-007\CADD\Bridge\31576007GP01.dgn

REVISIONS DESCRIPTION DATE BY





NOTES: 1. THE VERTICAL AND HORIZONTAL CLEARANCES SHALL BE DESIGNED TO MAINTAIN THE HYDRAULIC ADEQUACY OF THE EXISTING BC 1255 AND BC 1555.

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

SP03

CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005 F.A.P. STP-3057(6)N

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE


TYPICAL SECTION ALICEANNA STREET OVER HARFORD RUN


WR&A


SCALE: AS SHOWN DATE: JANUARY, 2014


WHITMAN, REQUARDT & ASSOCIATES, LLP

TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION SHEET 26 OF 62 N:\31576-007\CADD\Bridge\31576007TS01.dgn









REVISIONS DATE BY DESCRIPTION

GENERAL NOTES

SPECIFICATIONS:

ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH SHA SPECIFICATIONS DATED 2008, INCLUDING ALL REVISIONS THEREOF AND ADDITIONS THERETO AND

SPECIAL PROVISIONS FOR MATERIALS AND CONSTRUCTION.

AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS DATED 2012 (6th EDITION)

CONCRETE DESIGN: LOAD AND RESISTANCE FACTOR (LRFD) DESIGN

HL-93 PLUS 2" FUTURE WEARING SURFACE.

ALL CONCRETE FOR TOP SLAB SHALL BE MIX NO. 6 (4,500 PSI). ALL OTHER CONCRETE SHALL BE MIX NO. 3 (3,500 PSI.)

REINFORCING STEEL SHALL CONFORM TO A 615, GRADE 60. ALL SPLICES, NOT SHOWN, SHALL BE LAPPED AS PER BAR LAP CHARTS. MINIMUM

> COVER FOR ANY BAR SHALL BE 2" UNLESS OTHERWISE NOTED, WITH THE EXCEPTION OF BARS AT THE BOTTOM AND SIDES OF ALL FOOTINGS

WHICH SHALL HAVE 3" MINIMUM COVER.

REINFORCING STEEL DESIGN: Fy = 60,000 PSI.

FOR TIES AND STIRRUPS; STANDARD ACI BENDING TOLERANCES ARE MODIFIED TO PLUS (+) ZERO INCHES, MINUS (-) NORMAL ACI BENDING TOLERANCES.

ONLY GRADE 60 CAN BE USED ON THIS PROJECT

ALL REINFORCING STEEL IN THE TOP MAT OF THE TOP SLAB INCLUDING

TRUSS BARS SHALL BE EPOXY COATED.

ALL KEYS ARE NOMINAL SIZE.

ALL DIMENSIONS AFFECTED BY THE GEOMETRICS, AND/OR EXISTING STRUCTURE EXISTING STRUCTURE:

SHALL BE CHECKED IN THE FIELD BY THE CONTRACTOR, BEFORE ANY CONSTRUCTION IS DONE, AND BEFORE ANY REINFORCING STEEL, ETC., IS ORDERED AND FABRICATED. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO SUPPLY THE ENGINEER WITH ALL FIELD DIMENSIONS REQUIRED TO CHECK DETAIL DRAWINGS. THE ± MARKS SHOWN WITH DIMENSIONS

AND STATIONS DO NOT INDICATE ANY DEGREE OF PRECISION. THESE MARKS (\pm) INDICATE EXISTING DIMENSIONS AND STATIONS THAT MAY VARY AND DO REQUIRE FIELD VERIFICATION BY THE CONTRACTOR.

EXISTING STRUCTURE SHOWN IN LONG DASHED LINES.

PORTIONS OF EXISTING STRUCTURES SHOWN HATCHED, TO BE REMOVED.

EXISTING PLANS: FOR THE CONVENIENCE AND INFORMATION OF BIDDERS, PRINTS OF PLANS

OF THE EXISTING PERTINENT STRUCTURES ARE AVAILABLE AT THE CITY OF BALTIMORE, DEPARTMENT OF TRANSPORTATION, FOR THE CONTRACTOR'S REVIEW. NO RESPONSIBILITY FOR THEIR ACCURACY OR COMPLETENESS IS ASSUMED BY THE CITY OF BALTIMORE, DEPARTMENT OF TRANSPORTATION.

DIMENSIONS, DETAILS, ETC. AS SHOWN THEREON MAY NOT BE "AS BUILT"

THE DESIGN-BUILDER IS RESPONSIBLE FOR IDENTIFYING, LOCATING, AND RELOCATING, AS NECESSARY, ALL EXISTING UTILITIES WITHIN THE PROJECT

AREA. THE UTILITIES SHOWN HEREON ARE FOR REFERENCE ONLY AND THE CITY OF BALTIMORE, DEPARTMENT OF TRANSPORTATION, TAKES NO RESPONSIBILITY FOR THE COMPLETENESS OR ACCURACY OF THE UTILITY INFORMATION SHOWN

HEREON. UTILITIES SHOWN ARE BASED ON FIELD SURVEY INFORMATION. NO TEST-PITS WERE PERFORMED TO DETERMINE VERTICAL LOCATION OF UTILITIES SHOWN.

1. THE STAGING LIMITS SHOWN ARE SUGGESTED AND THE DESIGN—BUILDER SHALL MAKE THEIR OWN DETERMINATION OF THE REQUIRED STAGING LIMITS. IT IS THE RESPONSIBILITY OF THE DESIGN—BUILDER TO CONFIRM THAT THEIR PROPOSED LIMITS OF STAGING MEET ALL OF THE REQUIRED STRUCTURAL AND MAINTENANCE OF TRAFFIC PROVISIONS STIPULATED IN THE SPECIAL PROVISIONS.

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

SP07

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. BC410005 F.A.P. STP-3057(6)N

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE


GENERAL PLAN AND ELEVATION


UR®A WHITMAN, REQUARDT & ASSOCIATES, LLP

FLEET STREET OVER HARFORD RUN

SCALE: AS SHOWN DATE: JANUARY, 2014 TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION SHEET 30 OF 62

N:\31576-007\CADD\Bridge\31576007GP02.dgn





DRAWN BY: L.M.B.

EXAMINED BY: J.G.V./W.A.G.

REVISIONS

IO. DESCRIPTION DATE BY

NOTES:

PROPOSED MTA REDLINE TUNNELS NOT SHOWN FOR CLARITY. SEE SPECIAL PROVISIONS FOR MORE INFORMATION.

2. THE VERTICAL AND HORIZONTAL CLEARANCES SHALL BE DESIGNED TO MAINTAIN THE HYDRAULIC ADEQUACY OF THE EXISTING BC 1255 AND THE RIGID FRAME STRUCTURE.

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

SP08

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION

CONTRACT NO. TR12317

SHA. NO. BC410005

F.A.P. STP-3057(6)N

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE


TYPICAL SECTION


WHITMAN, REQUARDT & ASSOCIATES, LLP 801 Struck Struck Struck Movingon Movingon Moving and 2021 FLEET STREET OVER HARFORD RUN


SCALE: AS SHOWN DATE: JANUARY, 2014


TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET 31 OF 62

N:\31576-007\CADD\Bridge\31576007TS02.dgn









SPECIFICATIONS:

ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE MARYLAND STATE HIGHWAY ADMINISTRATION STANDARD SPECIFICATIONS FOR CONSTRUCTION AND MATERIAL DATED JULY 2008 AND ALL REVISIONS

AND ADDITIONS THERETO.

AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS. 6TH EDITION, DATED 2012 WITH ALL INTERIM REVISIONS.

CONCRETE DESIGN: LOAD AND RESISTANCE FACTOR DESIGN METHOD f'c=3500 PSI EXCEPT THAT IN BRIDGE DECK SLABS SUPPORTED BY STRINGERS IT SHALL BE 4500 PSI.

LOADING:

REINFORCING STEEL DESIGN: fy = 60,000 PSI.

STRUCTURAL STEEL DESIGN: LOAD AND RESISTANCE FACTOR DESIGN METHOD.

HL-93 WITH PROVISIONS FOR FUTURE 2" WEARING SURFACE AND 15 LB/SQ FT FOR

USE OF STEEL BRIDGE DECK FORMS WHICH REMAIN IN PLACE.

RATINGS:

RATINGS ARE BASED ON LOAD AND RESISTANCE FACTOR RATING METHOD.

LOAD TYPE	LRFR INVENTORY	LRFR OPERATING	
HL-93	RF≥1	RF≥1	
HS-20	RF≥1	RF≥1	
H-15	RF≥1	RF≥1	
MD TYPE 3 TRUCK	RF≥1	RF≥1	
MD TYPE 3S2	RF≥1	RF≥1	

CONCRETE:

ALL CONCRETE FOR ABUTMENT BACKWALLS AND PARAPETS AT ABUTMENTS AND ENTIRE SUPERSTRUCTURE SHALL BE SHA MIX NO. 6 (4500 PSI). ALL OTHER STRUCTURE CONCRETE SHALL BE SHA MIX NO. 3 (3500PSI).

REINFORCING STEEL SHALL CONFORM TO ASTM A 615, GRADE 60. ALL SPLICES NOT SHOWN SHALL BE LAPPED AS PER SHA BAR LAP CHARTS. MINIMUM COVER FOR ANY BAR SHALL BE 2" UNLESS OTHERWISE NOTED WITH THE EXCEPTION OF BARS AT THE TOP OF PIERS AND AT THE BOTTOM AND SIDES OF ALL FOOTINGS WHICH SHALL HAVE 3" MINIMUM COVER FOR TIES AND STIRRUPS, STANDARD ACIBENDING TOLERANCES ARE MODIFIED TO PLUS(+) ZERO INCHES, MINUS (-) NORMAL ACI BENDING TOLERANCES.

REINFORCING STEEL:

ONLY GRADE 60 CAN BE USED ON THIS PROJECT

REINFORCING STEEL IN THE FOLLOWING AREAS SHALL BE EPOXY COATED: ENTIRE SUPERSTUCTURE (INCLUDING PARAPETS AND END DIAPHRAGMS) ABUTMENT BACKWALLS

ALL BEARING SEAT PADS ABUTMENT BRIDGE SEAT AREAS PARAPET PORTION OF WINGWALLS

PIER CAPS LOCATED UNDER BRIDGE DECK ROADWAY JOINTS

KEYS:

ALL KEYS ARE NOMINAL SIZE.

STRUCTURAL STEEL:

STRUCTURAL STEEL SHALL CONFORM TO A 709 GRADE 50, INCLUDING THE ADDITIONAL REQUIREMENTS FOR CHARPY V-NOTCH TESTING OF M 270 FOR

PRIMARY LOAD CARRYING MEMBERS.

PAINT COLOR:

THE COLOR FOR THE FINISHED COAT SHALL MATCH FEDERAL STARDARD 595B COLOR NO. XXXXX.

EXISTING STRUCTURE: ALL DIMENSIONS AFFECTED BY THE GEOMETRICS, AND/OR LOCATION OF THE EXISTING STRUCTURE SHALL BE CHECKED IN THE FIELD BY THE CONTRACTOR, BEFORE ANY CONSTRUCTION IS DONE, AND BEFORE ANY MATERIAL IS ORDERED OR FABRICATED. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO SUPPLY THE ENGINEER WITH ALL FIELD DIMENSIONS REQUIRED TO CHECK DETAILED DRAWINGS. THE \pm MARKS SHOWN WITH DIMENSIONS AND STATIONS DO BNOT INDICATE ANY DEGREE OF PRECISION. THESE MARKS (土) INDICATE EXISTING DIMENSIONS AND STATIONS THAT MAY VARY AND DO REQUIRE FIELD VERIFICATION BY THE CONTRACTOR.

EXISTING STRUCTURE SHOWN IN LONG DASHED LINES.

NEW STRUCTURE SHOWN IN SOLID LINES.

PORTIONS OF EXISTING STRUCTURES SHOWN HATCHED TO BE REMOVED.

HYDROLOGICAL AND HYDRAULIC DATA:

HYDROLOGICAL AND HYDRAULIC DATA	
10 YEAR WSEL:	3.3
100-YEAR WSEL:	9.0
MEAN LOW WSEL:	1.02
AVERAGE WATERWAY INVERT: -	-7.1±
ROADWAY ELEVATION ON BRIDGE: LOWEST-	

30% SUBMITTAL NOT FOR CONSTRUCTION

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

REVISIONS

DATE BY

DESCRIPTION

CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 S.H.A. NO. PENDING F.A.P. PENDING

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE


GENERAL NOTES


RKSK Rummel, Klepper & Kahl,LLP 81 MOSHER STREET | BALTIMORE, MD 21217 PH: (410) 728-2900 FAX: (410) 728-3160 Engineers | Construction Managers | Planners | Scientists | SCALE: NONE


www.rkk.com

DATE: OCT 15, 2012 SHEET 36 OF 62

SP-13







ELEVATION

30% SUBMITTAL NOT FOR CONSTRUCTION

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

> CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 S.H.A. NO. PENDING F.A.P. PENDING

SP-14

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE PLAN AND ELEVATION ABUTMENT A


Rummel, Klepper & Kahl,LLP 81 MOSHER STREET | BALTIMORE, MD 21217 PH: (410) 728-2900 FAX: (410) 728-3160

RKSK


www.rkk.com


Engineers | Construction Managers | Planners | Scientists | SCALE: 1/4" =1'-0"

DATE: OCT 15, 2012 SHEET 37 OF 62



REVISIONS NO. DESCRIPTION DATE BY





SECTION B-B

DRAFT SUBMITTAL NOT FOR CONSTRUCTION


CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 S.H.A. NO. PENDING F.A.P. PENDING


SP-16

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE ABUTMENT TYPICAL SECTIONS

RKSK Rummel, Klepper & Kahl,LLP 81 MOSHER STREET | BALTIMORE, MD 21217 PH: (410) 728-2900 FAX: (410) 728-3160 Engineers | Construction Managers | Planners | Scientists | SCALE: ½" = 1'-0" www.rkk.com

DATE: OCT 15,2012 SHEET 39 OF 62






(LOOKING BACK STATION)

NOTE:

- DESIGN-BUILDER SHALL SPECIFY SHA STANDARD DECK SLAB.
 DESIGN-BUILDER SHALL SPECIFY SHA STANDARD PARAPET.
- 3. DESIGN-BUILDER SHALL SPECIFY SHA STANDARD SIDEWALK.
- 4. GIRDER CROSS-FRAMES NOT SHOWN FOR CLARITY.



7/15/2012 Nekam Vongo ong ngasa habbabbet tashar atasha bilas Carcert Struct Cadd Di ans ast-sand

REVISIONS DATE BY DESCRIPTION

INFORMATION UNDER DEVELOPMENT

30% SUBMITTAL NOT FOR CONSTRUCTION

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

SP-19

CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 S.H.A. NO. PENDING F.A.P. PENDING

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE

GEOTECHNICAL SITE CONSTRAINTS-1

RKSK Rummel, Klepper & Kahl, LLP 81 MOSHER STREET | BALTIMORE, MD 21217 PH: (410) 728-2900 FAX: (410) 728-3160

Engineers | Construction Managers | Planners | Scientists | SCALE: NONE

DATE: OCT 15, 2012

SHEET 42 OF 62

REVISIONS DATE BY DESCRIPTION

INFORMATION UNDER DEVELOPMENT

30% SUBMITTAL NOT FOR CONSTRUCTION

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

SP-20

CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 S.H.A. NO. PENDING F.A.P. PENDING

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE


GEOTECHNICAL SITE CONSTRAINTS-2


RKSK Rummel, Klepper & Kahl, LLP 81 MOSHER STREET | BALTIMORE, MD 21217 PH: (410) 728-2900 FAX: (410) 728-3160


Engineers | Construction Managers | Planners | Scientists | SCALE: NONE


DATE: OCT 15, 2012


SHEET 43 OF 62


















EXAMINED BY: T.J.M. / P.H.L


TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET 49 OF 62
































WITH POTENTIAL SWM

PLANTING BED AREAS

MEDIAN PLANTING AREAS

NONE

NONE

REVISIONS DATE BY DESCRIPTION

CRITICAL AREA TOTAL PROPOSED QUANTITIES

PROPOSED TREES 25 SHADE TREES AT 2.5" CAL. MIN.

3 FLOWERING TREES AT 6' HT. MIN. IN MEDIAN

TREES TO BE REMOVED 8.4" CAL. STREET TREE PLANTING AREAS 486 SF

STREET TREE PLANTING AREAS 1510 SF WITH POTENTIAL SWM

MEDIAN PLANTING AREAS NONE

NONE PLANTING BED AREAS

NON-CRITICAL AREA TOTAL PROPOSED QUANTITIES

PROPOSED TREES 47 SHADE TREES AT 2.5" CAL. MIN.

5 FLOWERING TREES AT 6' HT. MIN. IN MEDIAN 66.3" CAL.


STREET TREE PLANTING AREAS 2326 SF STREET TREE PLANTING AREAS 2404 SF

MEDIAN PLANTING AREAS 1711 SF

PLANTING BE AREA 666 SF (328 SF OF EXISTING AREA IS PERVIOUS)

NOTE:

- 1. SEE DETAILS 1 AND 4- TYPICAL STREET TREE DETAILS ON SHEET LD07
- 2. SEE DETAIL 2 TYPICAL BRICK PAVING PATTERN TYPE 1 AT PEDESTRIAN INTERSECTION ON SHEET LD07
- 3. SEE DETAIL 3 TYPICAL MEDIAN SECTION ON SHEET LD07
- 4. SALVAGE EXISTING GRANITE CURB FOR REUSE ON PROJECT (ESTIMATE 150 - 300 L.F. FOR REUSE). REFERENCE PERF. SPEC.
- 5. SALVAGE EXISTING COBBLES FOR REUSE ON PROJECT (ESTIMATE 1500 - 3000 S.F. FOR REUSE). REFERENCE PERF. SPEC.
- 6. SEE SWM PERFORMANCE SPECIFICATIONS FOR SWM TREE PIT DETAIL.



LD06

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. PENDING F.A.P. PENDING

CENTRAL AVENUE STREETSCAPE AND HARBOR POINT CONNECTOR BRIDGE

TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET 61 OF 62

LANDSCAPE PLAN STA. 129+50 - STA. 131+63

SCALE: 1"=20' DATE: OCTOBER, 2012

DRAWN BY: EXAMINED BY:

LEGEND

MEDIAN PLANTING

EXISTING TREE TO REMAIN


EXISTING TREE TO BE REMOVED

KEY MAP

The Stieff Silver Building. 800 Wyman Park Drive., Suite 100. Baltimore, MD 21211 410.235.6001

REVISIONS DATE BY DESCRIPTION

LIMITS OF BRICK BANDING IS FROM THE SOUTHERN PROJECT LIMITS APPROXIMATELY AT STA. 101+84 TO NORTHERN LIMITS AT APPROXIMATELY STA. 131+63. SIDE STREETS SHALL NOT RECEIVE BRICK BANDING BEYOND TYP. CORNER BRICK PAVING PATTERN. OMIT BRICK BANDS ACROSS DRIVEWAYS.




A. PREFERRED OFFSET FROM CURB

B. OFFSET NOT FEASIBLE - ALTERNATE

STREET TREE PLANTING BED AND BRICK BAND

NOT TO SCALE






NOT TO SCALE

- CONCRETE SIDEWALK **VARIES** HAND TIGHT BRICK PAVER IN STACKED BOND PATTERN -BRICK PAVERS IN 90 DEGREE HERRINGBONE PATTERN - CONCRETE CURB AND GUTTER - DETECTABLE WARNING PAVERS STACKED BOND PATTERN 6' MIN - EXTENT OF BRICK PAVING TO ALIGN TO CORNER, TYP. - PEDESTRIAN RAMP

CORNER BRICK PAVING PATTERN

NOT TO SCALE



MEDIAN PLANTING

NOT TO SCALE

DRAFT SUBMITTAL NOT FOR CONSTRUCTION

CITY OF BALTIMORE
DEPARTMENT OF TRANSPORTATION CONTRACT NO. TR12317 SHA. NO. PENDING

LD07

F.A.P. PENDING CENTRAL AVENUE STREETSCAPE AND

HARBOR POINT CONNECTOR BRIDGE MAHAN RYKIEL LANDSCAPE PLAN DETAILS The Stieff Silver Building. 800 Wyman Park Drive., Suite 100. Baltimore, MD 21211 410.235.6001

SCALE: 1"=20' DATE: OCTOBER, 2012

DRAWN BY: EXAMINED BY:

TRANSPORTATION ENGINEERING & CONSTRUCTION DIVISION | SHEET 62 OF 62